



TECHNICAL DATA

Wattage	Luminous Flux				Size (Ø X H) mm	Cut out (mm)
	2700K	3000K	4000K	6000K		
16W	1410	1440	1470	1500	105 X 72	90
24W	2080	2120	2165	2210	130 X 97	115
28W	2430	2480	2530	2580	138 X 107	125
32W	2780	2835	2890	2950	138 X 107	125
35W	3030	3090	3155	3220	138 X 110	125
42W	3635	3710	3785	3865	138 X 110	125
48W	4110	4195	4280	4365	185 X 132	170

Luminous Efficacy

>85lm/W

SDCM

<3

CRI

>83/93

Beam Angle

15°/18°/24°/38°/60°

Working Voltage

36 VDC

LED Driver

Remote

Control

Switched / 1-10V / DALI

Body Material

Die-cast Aluminium

Optics

PMMA

IP Rating

IP44

Working Temperature

-20°C to 40°C

Rated Life

50,000Hrs (L70)



ORDER INFORMATION

Product Code

BLU-COMFY-A-10-16W
 BLU-COMFY-A-13-24W/28W
 BLU-COMFY-A-13-32W
 BLU-COMFY-A-13-35W/42W
 BLU-COMFY-A-18-48W

X

8 - CRI 83+
 9 - CRI 93+

YY

27 -2700K
 30 -3000K
 40 -4000K
 60 -6000K

ZZ

15 - 15 Deg
 18 - 18 Deg
 24 - 24 Deg
 38 - 38 Deg
 60 - 60 Deg

Example: BLU-COMFY-A-10-16W-827-15

Specification subject to change without notice