



TECHNICAL DATA

<i>Product Code</i>	BLU-REX-11		
<i>Wattage</i>	8W / 12W / 14W		
<i>Luminous Flux</i>	8W	12W	14W
	2700K – 760lm	1140lm	1320lm
	3000K – 780lm	1160lm	1360lm
	4000K – 800lm	1180lm	1400lm
	6000K – 820lm	1200lm	1420lm
<i>Luminous Efficacy</i>	>90lm/W		
<i>SDCM</i>	<3		
<i>CRI</i>	>83/93		
<i>Beam Angle</i>	15° / 24° / 38° / 60°		
<i>Power Factor</i>	>0.95		
<i>Working Voltage</i>	220-240V AC, 50/60Hz		
<i>LED Driver</i>	Integral		
<i>Control</i>	Switched/1-10/DALI		
<i>Body Material</i>	Die Cast Aluminium		
<i>Optics</i>	PMMA Diffuser		
<i>IP Rating</i>	IP40		
<i>Working Temperature</i>	-20°C to 40°C		
<i>Rated Life</i>	50,000Hrs (L70)		

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-REX-11-8W	8 - CRI 83+	27 - 2700K	15 – 15 Deg
BLU-REX-11-10W	9 - CRI 93+	30 - 3000K	24 – 24 Deg
BLU-REX-11-14W		40 - 4000K	38 – 38 Deg
		60 - 6000K	60 – 60 Deg

Example: BLU-REX-11-8W-827-15

Specification subject to change without notice