



TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø X H)mm	Cut out (mm)
		2700K	3000K	4000K	5000K		
BLU-GLAZE-11	10W	900	915	930	950	110 x 43	90
BLU-GLAZE-11	12W	1090	1110	1130	1150	110 x 43	90
BLU-GLAZE-14	12W	1090	1110	1130	1150	140 x 54	125
BLU-GLAZE-14	13W	1250	1275	1300	1330	140 x 54	125
BLU-GLAZE-16	24W	2150	2190	2235	2280	162 x 64	145
BLU-GLAZE-16	28W	2510	2560	2610	2660	162 x 64	145
BLU-GLAZE-19	28W	2510	2560	2610	2660	193 x 76	165
BLU-GLAZE-23	32W	2875	2930	2990	3050	230 x 88	200

Luminous Efficacy

>85lm/W

SDCM

<3

CRI

>83/93

Beam Angle

40° / 60° (Clear Glass), 90° (Frosted Glass)

Working Voltage

36 VDC

LED Driver

Remote

Control

Switched / 1-10V / DALI

Body Material

Die-cast Aluminium

Diffuser

Clear Glass / Frosted Glass

IP Rating

IP65

Working Temperature

-20°C to 50°C

Rated Life

50,000Hrs (L70)

ORDER INFORMATION

Product Code

BLU-GLAZE-11-10W / 12W

BLU-GLAZE-14-12W / 13W

BLU-GLAZE-16-24W / 28W

BLU-GLAZE-19-28W

BLU-GLAZE-23-32W

X

8 - CRI 83+

9 - CRI 93+

YY

27 -2700K

30 -3000K

40 -4000K

50 -5000K

ZZ

IP65 - IP65

Example: BLU-GLAZE-11-10W-827-IP65

Specification subject to change without notice