

## TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (L X W X H)mm
		2700K	3000K	4000K	6000K	
BLU-PLANE-2X2	28W	2650	2695	2750	2800	595 X 595 X 10
BLU-PLANE-2X2	36W	3415	3480	3550	3600	595 X 595 X 10
BLU-PLANE-2X2	42W	3975	4050	4125	4200	595 X 595 X 10
BLU-PLANE-1X4	28W	2650	2695	2750	2800	1195 X 295 X 10
BLU-PLANE-1X4	36W	3415	3480	3550	3600	1195 X 295 X 10
BLU-PLANE-1X4	42W	3975	4050	4125	4200	1195 X 295 X 10
BLU-PLANE-2X4	28W	2650	2695	2750	2800	1195 X 595 X 10
BLU-PLANE-2X4	36W	3415	3480	3550	3600	1195 X 595 X 10
BLU-PLANE-2X4	42W	3975	4050	4125	4200	1195 X 595 X 10
BLU-PLANE-2X4	48W	4575	4650	4725	4800	1195 X 595 X 10
BLU-PLANE-2X4	55W	5275	5350	5425	5500	1195 X 595 X 10

Luminous Efficacy

>90lm/W

SDCM

<3

CRI

>83/93

Beam Angle

120°

Working Voltage

36 VDC

LED Driver

Remote

Control

Switched / 1-10V / DALI

Body Material

Extruded Aluminium

Diffuser

PS LGP with PS diffuser

IP Rating

IP44

Working Temperature

-20°C to 40°C

Rated Life

50,000Hrs (L70)

## ORDER INFORMATION

### Product Code

BLU-PLANE-2X2-28W/36W/42W

BLU-PLANE-1X4-28W/36W/42W

BLU-PLANE-2X4-28W/36W/42W/48W/55W

### X

8 - CRI 83+

9 - CRI 93+

### YY

27 -2700K

30 -3000K

40 -4000K

60 -6000K

### ZZ

IP44 - IP44

Example: BLU-PLANE-2X2-36W-827-IP44

Specification subject to change without notice

