



TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (A x B x C)mm
		2700K	3000K	4000K	6000K	
BLU-SOFTI-2X2	36W	3700	3800	3900	4000	595 X 595 X 40
BLU-SOFTI-1X4	36W	3700	3800	3900	4000	1195 X 295 X 40

<i>Luminous Efficacy</i>	>110lm/W
<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	90°
<i>Working Voltage</i>	36 VDC
<i>LED Driver</i>	Remote
<i>Control</i>	Switched / 1-10V / DALI
<i>Body Material</i>	Aluminium
<i>Optics</i>	PC diffuser
<i>IP Rating</i>	IP44
<i>Working Temperature</i>	-20°C to 40°C
<i>Rated Life</i>	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-SOFTI-2X2-36W	8 - CRI 83+	27 - 2700K	90 - 90 Deg
BLU-SOFTI-1X4-36W	9 - CRI 93+	30 - 3000K	
		40 - 4000K	
		60 - 6000K	

Example: BLU-SOFTI-2X2-36W-827

Specification subject to change without notice