



TECHNICAL DATA

Wattage	2500K	2700K	3000K	4000K	6000K
4.8W	480	490	500	510	520
7.2W	720	730	740	750	760
9.6W	960	970	980	990	1000
14.4W	1440	1450	1460	1470	1480
19.2W	1920	1930	1940	1950	1960

Luminous Efficacy	>100 lm/W
SDCM	< 3
CRI	>83 / 93
Beam Angle	120°
Working Voltage	24 VDC
LED Driver	Remote
Control	Switched / 0-10 / DALI
Body Material	Epoxy IP65, Silicone IP67
Optics	No secondary optics
IP Rating	IP20/IP65/IP67/IP68
Working Temperature	-20°C to 50°C
Rated Life	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-FLEXI-4.8W	8 - CRI 83+	25 - 2500K	IP20 - IP20
BLU-FLEXI-7.2W	9 - CRI 93+	27 - 2700K	IP65 - IP65
BLU-FLEXI-9.6W		30 - 3000K	IP67 - IP67
BLU-FLEXI-14.4W		40 - 4000K	IP68 - IP68
BLU-FLEXI-19.2W		60 - 6000K	

Example: BLU-FLEXI-4.8W-827-IP20



**ONE
BIN
ONLY**

Specification subject to change without notice