



# Flex-i HE

High Efficiency Flexible Strip



## TECHNICAL DATA

Wattage	2500K	2700K	3000K	4000K	6000K
4.8W	648	658	668	678	688
7.2W	972	982	992	1002	1012
9.6W	1296	1306	1316	1326	1336
14.4W	1944	1954	1964	1974	1984
19.2W	2592	2602	2612	2622	2632

<i>Luminous Efficacy</i>	>135 lm/W
<i>SDCM</i>	< 3
<i>CRI</i>	>83 / 93
<i>Beam Angle</i>	120°
<i>Working Voltage</i>	24 VDC
<i>LED Driver</i>	Remote
<i>Control</i>	Switched / 0-10 / DALI
<i>Body Material</i>	Epoxy IP65, Silicone IP67
<i>Optics</i>	No secondary optics
<i>IP Rating</i>	IP20/IP65/IP67/IP68
<i>Working Temperature</i>	-20°C to 50°C
<i>Rated Life</i>	50,000Hrs (L70)

## ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-FLEXI-HE-4.8W	8 - CRI 83+	25 - 2500K	IP20 - IP20
BLU-FLEXI-HE-7.2W	9 - CRI 93+	27 - 2700K	IP65 – IP65
BLU-FLEXI-HE-9.6W		30 - 3000K	IP67 – IP67
BLU-FLEXI-HE-14.4W		40 - 4000K	IP68 – IP68
BLU-FLEXI-HE-19.2W		60 – 6000K	

Example: BLU-FLEXI-HE-4.8W-827-IP20



ONE  
BIN  
ONLY

Specification subject to change without notice