



TECHNICAL DATA

<i>Product Code</i>	BLU-BEAM-P-SQL
<i>Wattage</i>	60W
<i>Luminous Flux</i>	2700K – 3970lm 3000K – 4000lm 4000K – 4030lm 6000K – 4060lm
<i>Luminous Efficacy</i>	> 60lm/W
<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	38° /45° /60°
<i>Power Factor</i>	>0.95
<i>Working Voltage</i>	220 - 240V AC
<i>LED Driver</i>	Integral (Switched) / Remote (Dimmable)
<i>Control</i>	Switched / 0-10V / DALI
<i>Body Material</i>	Die Cast Aluminum
<i>Diffuser</i>	Tempered Glass
<i>IP Rating</i>	IP66
<i>Working Temperature</i>	-20°C to 50°C
<i>Rated Life</i>	50,000Hrs (L70)



ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-BEAM-P-SQL-60W	8 - CRI 83+	27 - 2700K	38 – 38°
	9 - CRI 93+	30 - 3000K	45 – 45°
		40 - 4000K	60 – 60°
		60 - 6000K	

Example: BLU-BEAM-P-SQL-60W-827-60

Specification subject to change without notice