



TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø X H) mm
		2700K	3000K	4000K	5000K	
CEDO-P-R9	10W	830	850	870	890	90 X 100
CEDO-P-R9	15W	1520	1550	1580	1600	90 X 100
CEDO-P-R12	25W	2970	3000	3040	3070	120 X 110
CEDO-P-R16	30W	3120	3150	3180	3200	160 X 120
CEDO-P-R16	32W	3440	3480	3510	3540	160 X 120

<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	24°/36°/45°/60°
<i>Working Voltage</i>	240V AC, 50/60Hz
<i>LED Driver</i>	Integral (Switched), Remote (Dimmable)
<i>Power Factor</i>	>0.95
<i>Control</i>	Switched / 1-10V / DALI
<i>Body Material</i>	Die Cast Aluminium
<i>Diffuser</i>	Tempered Glass
<i>IP Rating</i>	IP65
<i>Working Temperature</i>	-20°C to 50°C
<i>Rated Life</i>	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-CEDO-P-R9-10W	8 - CRI 83+	27 -2700K	24 - 24 Deg
BLU-CEDO-P-R9-15W	9 - CRI 93+	30 -3000K	36 - 36 Deg
BLU-CEDO-P-R12-25W		40 -4000K	45 - 45 Deg
BLU-CEDO-P-R16-30W		50 -5000K	60 - 60 Deg
BLU-CEDO-P-R16-32W			

Example: BLU-CEDO-P-R9-10W-827-24-IP65

Specification subject to change without notice