



TECHNICAL DATA

<i>Product Code</i>	BLU-WALLZ		
<i>Wattage</i>	10W	20W	40W
<i>Luminous Flux</i>	2700K 1310lm	2620lm	5245lm
	3000K 1330lm	2670lm	5295lm
	4000K 1350lm	2720lm	5345lm
	5000K 1390lm	2770lm	5400lm
<i>Luminous Efficacy</i>	>131lm/W		
<i>SDCM</i>	<3		
<i>CRI</i>	>83		
<i>Beam Angle</i>	Asymmetric		
<i>Power Factor</i>	0.95		
<i>Working Voltage</i>	220-240VAC, 50/60Hz		
<i>LED Driver</i>	Integral		
<i>Control</i>	Switched, 0-10V		
<i>Body Material</i>	Die-cast Aluminum		
<i>Optics</i>	PMMA		
<i>IP Rating</i>	IP65		
<i>Working Temperature</i>	-15°C to 50°C		
<i>Rated Life</i>	180,000Hrs (L70) @ Ta 30°C		

ORDER INFORMATION

Product Code	YY	ZZ	AA
BLU-WALLZ	10W	8 - CRI 83+	27 – 2700K
	20W		30 – 3000K
	40W		40 – 4000K
			50 – 5000K

Example: BLU-WALLZ-40W-830

Specification subject to change without notice