



Mounting Sleeve

TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø X H) mm	Mounting Sleeve	Cut out (mm)
		2700K	3000K	4000K	6000K			
TITAN-R4	1W	70	72	74	76	43 X 53	41 X 60	41
TITAN-R6	3W	220	225	230	235	64 X 71	60 X 120	60
TITAN-R7	8W	590	600	615	630	79 X 79	71 X 130	71

<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	20°/40°/60°
<i>Working Voltage</i>	24 VDC
<i>LED Driver</i>	Remote
<i>Control</i>	Switched / 1-10V / DALI
<i>Body Material</i>	Stainless Steel 316L
<i>Diffuser</i>	Tempered Glass
<i>IP Rating</i>	IP68 (Immersion up to 5m water depth)
<i>Rated Life</i>	50,000Hrs (L70)



ORDER INFORMATION

Product Code	X	YY	ZZ
TITAN-R4-1W	8 - CRI 83+	27 -2700K	20 - 20 Deg
TITAN-R6-3W	9 - CRI 93+	30 -3000K	40 - 40 Deg
TITAN-R7-8W		40 -4000K	60 - 60 Deg
		60 -6000K	

Example: BLU-TITAN-R4-1W-827-20-IP68

Specification subject to change without notice