


ROOTZ R17/ S17 / R18


In Ground Uplighter





Rootz R17 (6*2W)



Rootz S17 (6*2W)



Rootz R18 (12*2W)



Mounting Sleeve

TECHNICAL DATA

Product Code	BLU-ROOTZ-R17 / S17 / R18	
Wattage	12W / 24W	
Luminous Flux	12W	24W
	2700K – 985lm	2050lm
	3000K – 1005lm	2070lm
	4000K – 1020lm	2090lm
	6000K – 1035lm	2110lm
Luminous Efficacy	>80lm/W	
SDCM	<3	
CRI	>83 / 93	
Beam Angle	18° / 24° / 38° / 60°	
Power Factor	>0.95	
Working Voltage	220 - 240V AC,	
LED Driver	Integral (Switched) / Remote (Dimmable)	
Control	Switched / 0-10V / DALI	
Body Material	Die Cast Aluminium	
Diffuser	Tempered Glass with HC Louvre	
IP Rating	IP67	
Working Temperature	-20°C to 50°C	
Rated Life	50,000Hrs (L70)	

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-ROOTZ-R17-12W	8 - CRI 80+	27 - 2700K	18 - 18 Deg
BLU-ROOTZ-S17-12W	9 - CRI 90+	30 - 3000K	24 - 24 Deg
BLU-ROOTZ-R18-24W		40 - 4000K	38 - 38 Deg
		60 - 6000K	60 - 60 Deg

Example: BLU-ROOTZ-R17-12W-830-18

Specification subject to change without notice