



## TECHNICAL DATA

Product Code	BLU-GLINE-65	
Wattage	50W / 75W	
Luminous Flux	50W	75W
	2700K – 4000lm	6000lm
	3000K – 4050lm	6075lm
	4000K – 4100lm	6100lm
	5000K – 4150lm	6150lm
Luminous Efficacy	>80 lm/w	
CRI	>83	
Beam Angle	10°/15°/30*/45°/60°/20X45°/10X60° / 18X55°	
Input Voltage	24 V DC	
LED Driver	Remote /Integral	
Control	Switched/1-10/DALI	
Body Material	Die Cast Aluminium	
Optics	PMMA with tempered glass diffuser	
IP Rating	IP66	
Working Temperature	-20°C to 50°C	
Rated Life	50,000Hrs (L70)	

## ORDER INFORMATION

Product Code	XX	YY	ZZ
BLU-GLINE-65-50W	8 – 83 Ra	27 – 2700K	10 - 10 Deg
BLU-GLINE-65-75W		30 – 3000K	15 – 15 Deg
		40 – 4000K	30 – 30 Deg
		50 – 5000K	45 – 45 Deg
			60 – 60 Deg
			ASY 1- 20X45Deg
			ASY 2- 10X60Deg
			ASY 3- 18X55Deg

Example: BLU-GLINE-65-50W-830-10

Specification subject to change without notice