# ROOTZ TL-L100Q

Trimless In-Ground Linear Uplight



## TECHNICAL DATA

| | |
|---|---|
| Product Code | BLU-ROOTZ- TL-L100Q |
| Wattage | 18W / 36W |
| Luminous Flux | **18W** **36W**<br>2700K – 1625lm 3250lm<br>3000K – 1650lm 3270lm<br>4000K – 1670lm 3290lm<br>6000K – 1700lm 3320lm |
| Luminous Efficacy | > 90lm/W |
| SDCM | <3 |
| CRI | >83 |
| Beam Angle | 5°/10°/15°/30°/60°/90°/15X45°/10X60° |
| Power Factor | >0.95 |
| Working Voltage | 24V DC |
| LED Driver | Remote |
| Control | Switched, DALI & 0-10V |
| Body Material | Aluminum |
| Optics | Tempered glass |
| IP Rating | IP67 |
| Working Temperature | -20°C to 50°C |
| Rated Life | 50,000Hrs (L70) |





## ORDER INFORMATION

| Product Code | X | YY | ZZ |
|---|---|---|---|
| BLU-ROOTZ-TL-L100Q-18W | 8 - CRI 83+ | 27 - 2700K | 5-5° |
| BLU-ROOTZ-TL-L100Q-36W | | 30 - 3000K | 10-10° |
| | | 40 - 4000K | 15-15° |
| | | 60 - 6000K | 30-30° |
| | | | 60-60° |
| | | | 90-90° |
| | | 15X45°-Asym | |
| | | 10X60°-Asym1 | |

Example: BLU-ROOTZ-TL-L100Q-18W-827-15

*Specification subject to change without notice*