



TECHNICAL DATA

<i>Product Code</i>	BLU-GLINE-38		
<i>Wattage</i>	18W / 24W / 36W		
<i>Luminous Flux</i>	18W	24W	36W
	2700K – 1480lm	1980lm	2980lm
	3000K – 1520lm	2020lm	3020lm
	4000K – 1560lm	2060lm	3060lm
	5000K – 1600lm	2100lm	3100lm
<i>Luminous Efficacy</i>	>80 lm/w; 100lm/w available on request		
<i>CRI</i>	>83		
<i>Beam Angle</i>	10°/15°/30°/45°/60°/20X45°/10X60° / 18X55°		
<i>Input Voltage</i>	24 V DC		
<i>LED Driver</i>	Remote		
<i>Control</i>	Switched/1-10/DALI		
<i>Body Material</i>	Extruded Aluminium		
<i>Optics</i>	PMMA with tempered glass diffuser		
<i>IP Rating / IK Rating</i>	IP66 / IK08		
<i>Working Temperature</i>	-20°C to 50°C		
<i>Rated Life</i>	50,000Hrs (L70)		

ORDER INFORMATION

Product Code	XX	YY	ZZ
BLU-GLINE-38-18W	8 – 83 Ra	27 – 2700K	10 - 10 Deg
BLU-GLINE-38-24W		30 – 3000K	15 – 15 Deg
BLU-GLINE-38-36W		40 – 4000K	30 – 30 Deg
		50 – 5000K	45 – 45 Deg
			60 – 60 Deg
			ASY 1- 20X45Deg
			ASY 2- 10X60Deg
			ASY 3- 18X55Deg

Example: BLU-GLINE-38-18W-830-ASY1

Specification subject to change without notice