



TECHNICAL DATA

Product Code	Wattage	Luminous Flux				Size L x W x H (mm)
		3000K	4000K	5000K	6000K	
BLU-PAC-S-60	20W	2275	2300	2325	2400	600 x 62 x 74
BLU-PAC-S-120	30W	3465	3500	3535	3570	1200 x 62 x 74
BLU-PAC-S-120	40W	4655	4700	4745	4790	1200 x 62 x 74
BLU-PAC-S-150	50W	5845	5900	5955	6010	1500 x 62 x 74
BLU-PAC-S-150	60W	7045	7100	7155	7210	1500 x 62 x 74

SDCM	<3
CRI	>83
Luminous Efficacy	>110lm/W
Beam Angle	120°
Working Voltage	AC200-240V
LED Driver	Integral
Power Factor	>0.9
Control	Switched / 1-10V / DALI, Option Available with Inbuilt Motion Sensor (MS)
Body Material	Polycarbonate
Diffuser	Polycarbonate
IP Rating	IP66
Working Temperature	-20°C to +50°C
Rated Life	50,000+ Hrs

ORDER INFORMATION

Product Code	XX	YY	ZZ
BLU-PAC-S-60-20W	8 - CRI 83+	30 -3000K	IP66 – IP66
BLU-PAC-S-120-30W		40 - 4000K	
BLU-PAC-S-120-40W		50 - 5000K	
BLU-PAC-S-150-50W		60 - 6000K	
BLU-PAC-S-150-60W			

Example: BLU-PAC-S-120-30W-830-IP66



Specification subject to change without notice