



TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø X H)mm	Cut out (mm)
		2700K	3000K	4000K	6000K		
BLU-VALUE-14	12W	1120	1140	1160	1180	145 X 56	130
BLU-VALUE-16	15W	1340	1360	1380	1400	160 X 66	140
BLU-VALUE-19	18W	1670	1690	1710	1730	190 X 77	165
BLU-VALUE-23	23W	2140	2160	2180	2200	230 X 82	200

Luminous Efficacy

>90lm/W

SDCM

<3

CRI

>83/93

Beam Angle

80°

Working Voltage

25-59 VDC

LED Driver

Remote

Control

Switched / 1-10V / DALI

Body Material

Aluminium

Optics

PC Diffuser

Reflector

Specular Aluminium / Matt Aluminium

IP Rating

IP44

Working Temperature

-20°C to 40°C

Rated Life

50,000Hrs (L70)

ORDER INFORMATION

Product Code

BLU-VALUE-14-12W

BLU-VALUE-16-15W

BLU-VALUE-19-18W

BLU-VALUE-23-23W

X

8 - CRI 83+

9 - CRI 93+

YY

27 -2700K

30 -3000K

40 -4000K

60 -6000K

Example: BLU-VALUE-14-12W-827

Specification subject to change without notice