





D2


HD2



CCRG



15W



20W



TECHNICAL DATA

Product Code	BLU-BULKZ-D2 / HD2 / CCRG		
Wattage	15W / 20W / 25W (System Wattage)		
Luminous Flux	15W	20W	25W
	2700K – 1300lm	1750lm	2025lm
	3000K – 1350lm	1800lm	2075lm
	4000K – 1400lm	1850lm	2150lm
	6000K – 1450lm	1900lm	2200lm
Luminous Efficacy	>85lm/W		
SDCM	<3		
CRI	>83		
Beam Angle	120°		
Power Factor	>0.95		
Working Voltage	220-240V AC, 50/60Hz		
LED Driver	Integral		
Control	Switched		
Body Material	Die-cast Aluminium		
Optics	PC Diffuser		
IP Rating	IP65		
Working Temperature	-20°C to 50°C		
Rated Life	50,000Hrs (L70)		

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-BULKZ-D2-15W	8 - CRI 83+	27 - 2700K	IP65 – IP65
BLU-BULKZ-D2-20W		30 - 3000K	
BLU-BULKZ-D2-25W		40 - 4000K	
BLU-BULKZ-HD2-15W		60 - 6000K	
BLU-BULKZ-HD2-20W			
BLU-BULKZ-HD2-25W			
BLU-BULKZ-D2-CCRG-15W			
BLU-BULKZ-D2-CCRG-20W			
BLU-BULKZ-D2-CCRG-25W			

Example: BLU-BULKZ-D2-15W-827-IP65

Specification subject to change without notice