



## TECHNICAL DATA

<i>Product Code</i>	BLU-PHOB-P		
<i>Wattage</i>	18W / 25W / 30W (System Wattage)		
<i>Luminous Flux</i>	18W	25W	30W
	2700K – 1550lm	2120lm	2550lm
	3000K – 1580lm	2140lm	2600lm
	4000K – 1605lm	2180lm	2650lm
	6000K – 1635lm	2220lm	2700lm
<i>Luminous Efficacy</i>	>85lm/W		
<i>SDCM</i>	<3		
<i>CRI</i>	>83/93		
<i>Beam Angle</i>	120°		
<i>Power Factor</i>	>0.95		
<i>Working Voltage</i>	220-240 VAC, 50/60Hz		
<i>LED Driver</i>	Integral		
<i>Control</i>	Switched		
<i>Body Material</i>	Polycarbonate		
<i>Diffuser</i>	Polycarbonate		
<i>IP Rating</i>	IP44		
<i>Dimensions</i>	A – Ø230mm, B – 30mm (15W & 25W)		
	A – Ø300mm, B – 30mm (30W)		
<i>Working Temperature</i>	-20°C to 40°C		
<i>Rated Life</i>	50,000Hrs (L70)		

## ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-PHOB-P-18W	8 - CRI 83+	27 - 2700K	IP44 – IP44
BLU-PHOB-P-25W	9 - CRI 93+	30 - 3000K	
BLU-PHOB-P-30W		40 - 4000K	
		60 - 6000K	

Example: BLU-PHOB-P-18W-827-IP44

Specification subject to change without notice