

TECHNICAL DATA


Product Code	BLU-FLEXI-CS
Wattage	9.6W
Luminous Flux	2700K - 940lm 3000K - 960lm 4000K - 980lm 6000K - 1000lm
SDCM	<3
Luminous Efficacy	>95 lm/W
CRI	83 / 93
Beam Angle	120°
Strip Width	5mm – IP20 / 8mm -IP65
Working Voltage	24 VDC
LED Driver	Remote
Control	Switched / 0-10 / DALI
Body Material	PP Sleeve (IP65)
IP Rating	IP20/ IP65
Working Temperature	-20°C to 50°C
Rated Life	50,000Hrs (L80)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-FLEXI-CS-9.6W	8 – CRI 83	27 - 2700K	IP20
	9 – CRI 93	30 - 3000K	IP65
		40 - 4000K	
		60 - 6000K	

Example: BLU-FLEXI-CS-9.6W-830-IP65

Specification subject to change without notice



TECHNICAL DETAIL

Description	Material	Code Reference
Aluminium Profile	6063-T5 Aluminium	BLU-EXTRU-CH
Diffuser	OPAL / Clear	BLU-EXTRU-DF
End Cap	Plastic / Aluminium	BLU-EXTRU-EC
Monting Clip	Stainless Steel	BLU-EXTRU-CLP

ORDER INFORMATION

Product Code	XX	YY
BLU-EXTRU-CH	A 2410	0.5M
BLU-EXTRU-DF	A 2410	1M
		1.5M
		2M
		2.5M
		3M

Example: BLU-EXTRU-CH-A2410-1M

Specification subject to change without notice