



4 Head /6 Head



### TECHNICAL DATA

Wattage	Luminous Flux				Ø X A X B X C
	2700K	3000K	4000K	6000K	
5W	405	425	445	465	50 X 125 X 210 X 292
10W	810	830	850	870	50 X 125 X 210 X 292
15W	1215	1235	1255	1275	50 X 125 X 210 X 292
20W	1620	1640	1660	1680	90 X 168 X 260 X 398
30W	2430	2450	2470	2490	108 X 220 X 260 X 410

Luminous Efficacy	> 80lm/W
SDCM	<3
CRI	83 / 93
Beam Angle	15°/24°/38°/45°/60°
Working Voltage	24VDC / 240VAC
LED Driver	Integral
Control	Switched (Integral) /1-10/DALI (Remote)
Body Material	Die-cast Aluminium
Diffuser	Tempered glass
Accessories	Cowl (C), Spike (S), Tree Strap (TS)
IP Rating	IP66
Working Temperature	-20°C to 50°C
Rated Life	50,000Hrs (L70)

### ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-SPEAR-RL5-5W	8 - CRI 83	27 - 2700K	15 - 15 Deg
BLU-SPEAR-RL5-10W	9 - CRI 93	30 - 3000K	24 - 24 Deg
BLU-SPEAR-RL5-15W		40 - 4000K	38 - 38 Deg
BLU-SPEAR-RL9-20W		60 - 6000K	45 - 45 Deg
BLU-SPEAR-RL10-30W			60 - 60 Deg

Example: BLU-SPEAR-RL5-5W-827-15

Specification subject to change without notice