



TECHNICAL DATA

<i>Product Code</i>	BLU-BEAM-SQ-Q	
<i>Wattage</i>	50W	100W
<i>Luminous Flux</i>	3000K – 4500lm	9000lm
	4000K – 4550lm	9100lm
	5000K – 4600lm	9200lm
	6000K – 4650lm	9300lm
<i>Luminous Efficacy</i>	>90lm/W	
<i>SDCM</i>	<3	
<i>CRI</i>	>83	
<i>Beam Angle</i>	5°/10°/ 15°/ 30°/ 45°/ 60°/10x30/10x60	
<i>Power Factor</i>	>0.95	
<i>Working Voltage</i>	220 - 240V AC, 50/60Hz	
<i>LED Driver</i>	Integral	
<i>Control</i>	Non-dimmable	
<i>Body Material</i>	Die Cast Aluminium	
<i>Diffuser</i>	Tempered Glass	
<i>IP Rating</i>	IP66	
<i>Working Temperature</i>	-20°C to 50°C	
<i>Rated Life</i>	50,000Hrs (L70)	

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-BEAM-SQ-20Q-50W	8 - CRI 80+	30 - 3000K	5 - 5°
BLU-BEAM-SQ-24Q-100W		40 - 4000K	10 - 10°
		50 - 5000K	15 - 15°
		60 - 6000K	30 - 30°
			45 - 45°
			60 - 60°
			ASY2 -10X60°

Example: BLU-BEAM-SQ-20Q-50W-830-5-IP66

Specification subject to change without notice