



TECHNICAL DATA

<i>Product Code</i>	BLU-BEAM-SQ-Q10	
<i>Wattage</i>	12W / 15W	
<i>Luminous Flux</i>	12W	15W
	2700K – 1220 lm	1540 lm
	3000K – 1250 lm	1560 lm
	4000K – 1280 lm	1580 lm
	6000K – 1300 lm	1600 lm
<i>Luminous Efficacy</i>	>100 lm/W	
<i>SDCM</i>	<3	
<i>CRI</i>	>83/93	
<i>Beam Angle</i>	5° / 10° / 15° / 30° / 45° / 60°	
<i>Input Voltage</i>	220-240VAC, 50/60Hz	
<i>LED Driver</i>	Integral / Remote	
<i>Control</i>	Switched / 0-10V / DALI	
<i>Body Material</i>	Die-Cast Aluminum	
<i>Optics</i>	Tempered Glass	
<i>IP Rating</i>	IP65	
<i>Working Temperature</i>	-20°C to 50°C	
<i>Rated Life</i>	50,000Hrs (L70)	

IK07

ORDER INFORMATION

Product Code	XX	YY	ZZ
BLU-BEAM-SQ-Q10-12W	8-83CRI	27-2700K	5 – 5°
BLU-BEAM-SQ-Q10-15W	9-93CRI	30-3000K	10 – 10°
		40-4000K	15 – 15°
		60-6000K	30 – 30°
			45 – 45°
			60 – 60°

Example: BLU-BEAM-SQ-Q10-12W-827-5

Specification subject to change without notice