



TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø x A x B x C x D)mm
		2700K	3000K	4000K	6000K	
BLU-BEAM-P-R7K	6W	540	550	560	570	70 X 134 X 48 X 104 X 40
BLU-BEAM-P-R7K	8W	720	730	740	750	70 X 134 X 48 X 104 X 40
BLU-BEAM-P-R9K	10W	900	905	910	915	90 X 149 X 59 X 130 X 50
BLU-BEAM-P-R9K	20W	1800	1810	1820	1830	90 X 149 X 59 X 130 X 50
BLU-BEAM-P-R12K	25W	2250	2260	2270	2280	120 X 198 X 78 X 173 X 65
BLU-BEAM-P-R12K	30W	2700	2710	2720	2730	120 X 198 X 78 X 173 X 65
BLU-BEAM-P-R16K	40W	3600	3610	3620	3630	160 X 249 X 99.4 X 232 X 82
BLU-BEAM-P-R16K	45W	4050	4060	4070	4080	160 X 249 X 99.4 X 232 X 82
BLU-BEAM-P-R25K	80W	7200	7210	7220	7230	250 X 333 X 222 X 235 X 90
BLU-BEAM-P-R25K	85W	7650	7660	7670	7680	250 X 333 X 222 X 235 X 90
BLU-BEAM-P-R30K	100W	9000	9010	9020	9030	300 X 390 X 260 X 287 X 108
BLU-BEAM-P-R30K	110W	9900	9910	9920	9930	300 X 390 X 260 X 287 X 108

TECHNICAL DATA

<i>Luminous Efficacy</i>	>90lm/W
<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	8°/10°/12°/15°/24°/38°/60°
<i>Working Voltage</i>	240V AC, 50/60Hz
<i>LED Driver</i>	Integral / Remote
<i>Power Factor</i>	>0.95
<i>Control</i>	Switched (Integral)/ 1-10V / DALI (Remote)
<i>Body Material</i>	Die-cast Aluminium
<i>Diffuser</i>	Tempered Glass
<i>IP Rating</i>	IP66
<i>Working Temperature</i>	-20°C to 50°C
<i>Rated Life</i>	50,000Hrs (L70)

IK07

ACCESSORIES

SPIKE



BEVEL CUT HOOD



TREE POLE STRAP



ANTI GLARE LOUVER



ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-BEAM-P-R7K-6W/8W	8 - CRI 83+	27 -2700K	8 - 8 Deg
	9 - CRI 93+	30 -3000K	10 - 10 Deg
BLU-BEAM-P-R9K-10W/20W		40 -4000K	12 - 12 Deg
		60 -6000K	15 - 15 Deg
BLU-BEAM-P-R12K-25W/30W			24 - 24 Deg
			38 - 38 Deg
			60 - 60 Deg
BLU-BEAM-P-R16K-40W/45W			
BLU-BEAM-P-R25K-80W/85W			
BLU-BEAM-P-R30K-100W/110W			

Example: BLU-BEAM-P-R7K-6W-827-8

Specification subject to change without notice