

PHOBOS ov


Ceiling / Wall Mounted Light



IK08



IP Rating



LED



Beam Angle



Base Material



CE



RoHS



Rated Life



Warranty

Key Features:

- Made from Polycarbonate ensuring durability and a sleek finish.
- IP54 rated, protecting against dust and water ingress.
- Designed to operate in temperatures ranging from -20°C to 50°C.
- Integral LED Driver
- Rated life at 50,000Hrs (L70)
- 120° Beam Angle

Luminous Efficacy	80lm/W	Control	Switched
SDCM	<3	Body Material	Polycarbonate
CRI	>83	Optics	Polycarbonate
Beam Angle	120°	IP Rating	IP65
Power Factor	>0.95	Working Temp	-20°C to 50°C
Working Voltage	220-240 VAC, 50/60Hz	Rated Life	50,000Hrs (L70)
LED Driver	Integral		

PHOBOS E

Ceiling / Wall Mounted Light

Technical Data

Product Code	Wattage	Luminous Flux				Size (L x W x H) mm
		2700K	3000K	4000K	6000K	
BLU-PHOB-OV	8W	640	660	680	700	200.3x100.3x55
BLU-PHOB-OV	12W	960	980	1000	1020	230.3x105.3x55
BLU-PHOB-OV	15W	1200	1240	1280	1320	230.3x105.3x55
BLU-PHOB-OV	18W	1440	1480	1520	1560	230.3x105.3x55

Ordering Code:

Product Code	X	YY	ZZ
BLU-PHOB-OV-8W	8 - CRI 83+	27 -2700K	IP65 - IP65
BLU-PHOB-OV-12W		30 -3000K	
BLU-PHOB-OV-15W		40 -4000K	
BLU-PHOB-OV-18W		60 -6000K	

Example: BLU-PHOB-OV-8W-827-IP54

Typical Applications:



Homes



Offices



Commercial



Malls



Schools



Hospitals



Hotels

Our products use the following LED Chips & Drivers

LED Chips:



LED Drivers:

