



TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø X H)mm	Cut out (mm)
		2700K	3000K	4000K	5000K		
BLU-COMFY-10	16W	1410	1440	1470	1500	105 X 90	90
BLU-COMFY-12	17W	1498	1530	1561	1593	125 X 122	115
BLU-COMFY-16	28W	2430	2480	2530	2580	138 X 127	150
BLU-COMFY-19	28W	2430	2480	2530	2580	165 X 140	170
BLU-COMFY-19	32W	2780	2835	2890	2950	165 X 140	170
BLU-COMFY-23	35W	3030	3090	3155	3220	233 X 177	210
BLU-COMFY-23	42W	3635	3710	3785	3865	233 X 177	210

Luminous Efficacy

>85lm/W ; 120 lm/W available on request

SDCM

<3

CRI

>83/93

Beam Angle

15°/24°/38°/60°

Working Voltage

36 VDC

LED Driver

Remote

Control

Switched / 1-10V / DALI

Body Material

Die-cast Aluminium

Optics

PMMA

IP Rating

IP44

Working Temperature

-20°C to 40°C

Rated Life

50,000Hrs (L70)

ORDER INFORMATION

IK02

Product Code	X	YY	ZZ
BLU-COMFY-10 16W	8 - CRI 83+	2700K	15 - 15 Deg
BLU-COMFY-12 17W	9 - CRI 93+	3000K	24 - 24 Deg
BLU-COMFY-16 28W		4000K	38 - 38 Deg
BLU-COMFY-19 28W		5000K	60 - 60 Deg
BLU-COMFY-19 32W			
BLU-COMFY-23 35W			
BLU-COMFY-23 42W			

Example: BLU-COMFY-10-16W-827-15

Specification subject to change without notice