



TECHNICAL DATA

<i>Product Code</i>	BLU-SAT-23		
<i>Wattage</i>	28W / 35W		
<i>Luminous Flux</i>		28W	35W
	2700K – 2510lm	3135lm	
	3000K – 2560lm	3195lm	
	4000K – 2610lm	3260lm	
	5000K – 2660lm	3325lm	
<i>Luminous Efficacy</i>	>90lm/W		
<i>SDCM</i>	<3		
<i>CRI</i>	>83/93		
<i>Beam Angle</i>	60°		
<i>Working Voltage</i>	36 VDC		
<i>LED Driver</i>	Remote		
<i>Control</i>	Switched / 1-10V / DALI		
<i>Body Material</i>	Die-cast Aluminium		
<i>Optics</i>	Multifaceted reflector with tempered glass cover		
<i>IP Rating</i>	IP44		
<i>Working Temperature</i>	-20°C to 40°C		
<i>Rated Life</i>	50,000Hrs (L70)		

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-SAT-23-28W	8 - CRI 83+	27 - 2700K	60 - 60 Deg
BLU-SAT-23-35W	9 - CRI 93+	30 - 3000K	
		40 - 4000K	
		50 - 5000K	

Example: BLU-SAT-23-28W-827-60

Specification subject to change without notice