



TECHNICAL DATA

| | |
|----------------------------|--|
| <i>Product Code</i> | BLU-LUVR-2X2 |
| <i>Wattage</i> | 28W |
| <i>Luminous Flux</i> | 2700K – 3205lm 3000K – 3270lm 4000K – 3335lm 5000K – 3400lm |
| <i>Luminous Efficacy</i> | >100lm/W |
| <i>SDCM</i> | <3 |
| <i>CRI</i> | >83/93 |
| <i>Beam Angle</i> | 85° |
| <i>Working Voltage</i> | 36 VDC |
| <i>LED Driver</i> | Remote |
| <i>Control</i> | Switched / 1-10V / DALI |
| <i>Body Material</i> | Sheet metal with Die cast aluminium |
| <i>Optics</i> | Specular reflector |
| <i>IP Rating</i> | IP20 |
| <i>Working Temperature</i> | -20°C to 40°C |
| <i>Rated Life</i> | 50,000Hrs (L70) |

ORDER INFORMATION

| Product Code | X | YY | ZZ |
|---------------------|-------------|------------|-------------|
| BLU-LUVR-2X2-28W | 8 - CRI 83+ | 27 - 2700K | 85 - 85 Deg |
| | 9 - CRI 93+ | 30 - 3000K | |
| | | 40 - 4000K | |
| | | 60 - 6000K | |

Example: BLU-LUVR-2X2-28W-827

Specification subject to change without notice