



**TECHNICAL DATA**

<i>Product Code</i>	BLU-SOFTI-2X2
<i>Wattage</i>	40W
<i>Luminous Flux</i>	2700K – 4710lm 3000K – 4805lm 4000K – 4900lm 6000K – 5000lm
<i>Luminous Efficacy</i>	>100lm/W
<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	120°
<i>Working Voltage</i>	36 VDC
<i>LED Driver</i>	Remote
<i>Control</i>	Switched / 1-10V / DALI
<i>Body Material</i>	Sheet metal with Die-cast Aluminium
<i>Optics</i>	PC diffuser
<i>IP Rating</i>	IP44
<i>Working Temperature</i>	-20°C to 40°C
<i>Rated Life</i>	50,000Hrs (L70)

**ORDER INFORMATION**

<b>Product Code</b>	<b>X</b>	<b>YY</b>	<b>ZZ</b>
BLU-SOFTI-2X2-40W	8 - CRI 83+	27 - 2700K	120 - 120 Deg
	9 - CRI 93+	30 - 3000K	
		40 - 4000K	
		60 - 6000K	

Example: BLU-SOFTI-2X2-40W-827

Specification subject to change without notice