



TECHNICAL DATA

<i>Product Code</i>	BLU-FLEXI-HE																									
<i>Wattage</i>	4.8W / 9.6W / 14.4W / 18W																									
<i>Luminous Flux</i>	<table border="1"> <tr> <td></td> <td>4.8W</td> <td>9.6W</td> <td>14.4W</td> <td>18W</td> </tr> <tr> <td>2700K-</td> <td>620lm</td> <td>1225lm</td> <td>1830lm</td> <td>2185lm</td> </tr> <tr> <td>3000K-</td> <td>635lm</td> <td>1250lm</td> <td>1865lm</td> <td>2230lm</td> </tr> <tr> <td>4000K-</td> <td>645lm</td> <td>1275lm</td> <td>1900lm</td> <td>2275lm</td> </tr> <tr> <td>6000K-</td> <td>660lm</td> <td>1300lm</td> <td>1940lm</td> <td>2320lm</td> </tr> </table>		4.8W	9.6W	14.4W	18W	2700K-	620lm	1225lm	1830lm	2185lm	3000K-	635lm	1250lm	1865lm	2230lm	4000K-	645lm	1275lm	1900lm	2275lm	6000K-	660lm	1300lm	1940lm	2320lm
	4.8W	9.6W	14.4W	18W																						
2700K-	620lm	1225lm	1830lm	2185lm																						
3000K-	635lm	1250lm	1865lm	2230lm																						
4000K-	645lm	1275lm	1900lm	2275lm																						
6000K-	660lm	1300lm	1940lm	2320lm																						
<i>Luminous Efficacy</i>	>130lm/W																									
<i>SDCM</i>	<3																									
<i>CRI</i>	>83/93																									
<i>Beam Angle</i>	120°																									
<i>Working Voltage</i>	24 VDC																									
<i>LED Driver</i>	Remote																									
<i>Control</i>	Switched / 1-10V / DALI																									
<i>Body Material</i>	Epoxy IP65, Silicone IP67																									
<i>Optics</i>	No secondary specs																									
<i>IP Rating</i>	IP20 / IP65 / IP67																									
<i>Working Temperature</i>	-20°C to 40°C																									
<i>Rated Life</i>	50,000Hrs (L70)																									

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-FLEXI-HE-4.8W	8 - CRI 83+	27 - 2700K	IP20
BLU-FLEXI-HE-9.6W	9 - CRI 93+	30 - 3000K	IP65
BLU-FLEXI-HE-14.4W		40 - 4000K	IP67
BLU-FLEXI-HE-18W		60 - 6000K	

Example: BLU-FLEXI-HE-4.8W-827-IP20

Specification subject to change without notice