



TECHNICAL DATA

<i>Product Code</i>	BLU-TRAKZ-8
<i>Wattage</i>	20W (System Wattage)
<i>Luminous Flux</i>	2700K – 2165lm 3000K – 2210lm 4000K – 2255lm 5000K – 2300lm
<i>Luminous Efficacy</i>	>100lm/W
<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	12°/24°/45°
<i>Power Factor</i>	>0.95
<i>Working Voltage</i>	220-240 VAC, 50/60Hz
<i>LED Driver</i>	Integral
<i>Control</i>	Switched / 1-10V / DALI
<i>Body Material</i>	Die-cast Aluminium
<i>Optics</i>	Multifaceted reflector with PC cover
<i>IP Rating</i>	IP20
<i>Working Temperature</i>	-20°C to 40°C
<i>Rated Life</i>	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-TRAKZ-8-20W	8 - CRI 83+	27 - 2700K	12 - 12 Deg
	9 - CRI 93+	30 - 3000K	24 - 24 Deg
		40 - 4000K	45 - 45 Deg
		60 - 6000K	

Example: BLU-TRAKZ-8-20W-827-12

Specification subject to change without notice