



Clima Proof 150

Weatherproof



TECHNICAL DATA

<i>Product Code</i>	BLU-CLIMA-150
<i>Wattage</i>	60W (System Wattage)
<i>Luminous Flux</i>	2700K – 7060lm 3000K – 7205lm 4000K – 7350lm 6000K – 7500lm
<i>Luminous Efficacy</i>	>100lm/W
<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	120°
<i>Power Factor</i>	>0.95
<i>Working Voltage</i>	220-240 VAC, 50/60Hz
<i>LED Driver</i>	Integral
<i>Control</i>	Switched / 1-10V / DALI
<i>Body Material</i>	Extruded Aluminium
<i>Optics</i>	PC diffuser
<i>IP Rating</i>	IP65
<i>Working Temperature</i>	-20°C to 50°C
<i>Rated Life</i>	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-CLIMA-150-60W	8 - CRI 83+	27 - 2700K	120 - 120 Deg
	9 - CRI 93+	30 - 3000K	
		40 - 4000K	
		60 - 6000K	

Example: BLU-CLIMA-150-60W-827

Specification subject to change without notice