



# Phobos 28

Ceiling Light



## TECHNICAL DATA

<i>Product Code</i>	BLU-PHOB-28															
<i>Wattage</i>	15W / 18W / 24W (System Wattage)															
<i>Luminous Flux</i>	<table><tr><td>15W</td><td>18W</td><td>24W</td></tr><tr><td>2700K – 1125lm</td><td>1350lm</td><td>1800lm</td></tr><tr><td>3000K – 1150lm</td><td>1380lm</td><td>1840lm</td></tr><tr><td>4000K – 1175lm</td><td>1405lm</td><td>1880lm</td></tr><tr><td>6000K – 1200lm</td><td>1435lm</td><td>1920lm</td></tr></table>	15W	18W	24W	2700K – 1125lm	1350lm	1800lm	3000K – 1150lm	1380lm	1840lm	4000K – 1175lm	1405lm	1880lm	6000K – 1200lm	1435lm	1920lm
15W	18W	24W														
2700K – 1125lm	1350lm	1800lm														
3000K – 1150lm	1380lm	1840lm														
4000K – 1175lm	1405lm	1880lm														
6000K – 1200lm	1435lm	1920lm														
<i>Luminous Efficacy</i>	>80lm/W															
<i>SDCM</i>	<3															
<i>CRI</i>	>83/93															
<i>Beam Angle</i>	120°															
<i>Power Factor</i>	>0.95															
<i>Working Voltage</i>	220-240 VAC, 50/60Hz															
<i>LED Driver</i>	Integral															
<i>Control</i>	Switched / 1-10V / DALI															
<i>Body Material</i>	PC															
<i>Optics</i>	PC Diffuser															
<i>IP Rating</i>	IP44															
<i>Working Temperature</i>	-20°C to 40°C															
<i>Rated Life</i>	50,000Hrs (L70)															

## ORDER INFORMATION

<b>Product Code</b>	<b>X</b>	<b>YY</b>	<b>ZZ</b>
BLU-PHOB-28-15W	8 - CRI 83+	27 - 2700K	120 - 120Deg
BLU-PHOB-28-18W	9 - CRI 93+	30 - 3000K	
BLU-PHOB-28-24W		40 - 4000K	
		60 - 6000K	

Example: BLU-PHOB-28-15W-827

Specification subject to change without notice