



Deimos 28B

Ceiling Light



TECHNICAL DATA

<i>Product Code</i>	BLU-DEIM-28B																				
<i>Wattage</i>	15W / 18W / 24W (System Wattage)																				
<i>Luminous Flux</i>	<table><tr><td></td><td>15W</td><td>18W</td><td>24W</td></tr><tr><td>2700K –</td><td>1125lm</td><td>1350lm</td><td>1800lm</td></tr><tr><td>3000K –</td><td>1150lm</td><td>1380lm</td><td>1840lm</td></tr><tr><td>4000K –</td><td>1175lm</td><td>1405lm</td><td>1880lm</td></tr><tr><td>6000K –</td><td>1200lm</td><td>1435lm</td><td>1920lm</td></tr></table>		15W	18W	24W	2700K –	1125lm	1350lm	1800lm	3000K –	1150lm	1380lm	1840lm	4000K –	1175lm	1405lm	1880lm	6000K –	1200lm	1435lm	1920lm
	15W	18W	24W																		
2700K –	1125lm	1350lm	1800lm																		
3000K –	1150lm	1380lm	1840lm																		
4000K –	1175lm	1405lm	1880lm																		
6000K –	1200lm	1435lm	1920lm																		
<i>Luminous Efficacy</i>	>80lm/W																				
<i>SDCM</i>	<3																				
<i>CRI</i>	>83/93																				
<i>Beam Angle</i>	120°																				
<i>Power Factor</i>	>0.95																				
<i>Working Voltage</i>	220-240 VAC, 50/60Hz																				
<i>LED Driver</i>	Integral																				
<i>Control</i>	Switched																				
<i>Body Material</i>	PC																				
<i>Optics</i>	PC diffuser																				
<i>IP Rating</i>	IP44																				
<i>Working Temperature</i>	-20°C to 40°C																				
<i>Rated Life</i>	50,000Hrs (L70)																				

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-DEIM-28B-15W	8 - CRI 83+	27 - 2700K	120 - 120Deg
BLU-DEIM-28B-18W	9 - CRI 93+	30 - 3000K	
BLU-DEIM-28B-24W		40 - 4000K	
		60 - 6000K	

Example: BLU-DEIM-28B-15W-827

Specification subject to change without notice