



TECHNICAL DATA

<i>Product Code</i>	BLU-ECOB			
<i>Wattage</i>	100W / 150W / 200W / 250W			
<i>Luminous Flux</i>	100W	150W	200W	250W
	3000K – 17470lm	26200lm	34935lm	43655lm
	4000K – 17645lm	26465lm	35285lm	44105lm
	5000K – 17820lm	26730lm	35640lm	44550lm
	6000K – 18000lm	27000lm	36000lm	45000lm
<i>Luminous Efficacy</i>	>180lm/W			
<i>SDCM</i>	<4			
<i>CRI</i>	>80			
<i>Beam Angle</i>	120°			
<i>Power Factor</i>	>0.95			
<i>Working Voltage</i>	220-240 VAC, 50/60Hz			
<i>LED Driver</i>	Integral			
<i>Control</i>	Switched / 1-10V / DALI			
<i>Body Material</i>	Die-cast Aluminium			
<i>Optics</i>	PMMA			
<i>IP Rating</i>	IP66			
<i>Working Temperature</i>	-20°C to 50°C			
<i>Rated Life</i>	50,000Hrs (L70)			

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-ECOB-100W	8 - CRI 80+	30 - 3000K	120 - 120Deg
BLU-ECOB-150W		40 - 4000K	
BLU-ECOB-200W		50 - 5000K	
BLU-ECOB-250W		60 - 6000K	

Example: BLU-ECOB-100W-827

Specification subject to change without notice