



TECHNICAL DATA

<i>Product Code</i>	BLU-PTRC		
<i>Wattage</i>	40W / 50W / 60W		
<i>Luminous Flux</i>	40W	50W	60W
	3000K – 5490lm	6370lm	7350lm
	4000K – 5545lm	6435lm	7425lm
	5000K – 5600lm	6500lm	7500lm
<i>Luminous Efficacy</i>	>140lm/W		
<i>SDCM</i>	<5		
<i>CRI</i>	>80		
<i>Beam Angle</i>	60°/90°/110°		
<i>Power Factor</i>	>0.95		
<i>Working Voltage</i>	220-240 VAC, 50/60Hz		
<i>LED Driver</i>	Integral		
<i>Control</i>	Switched / 1-10V / DALI		
<i>Body Material</i>	Die-cast Aluminium		
<i>Optics</i>	PMMA		
<i>IP Rating</i>	IP66		
<i>Working Temperature</i>	-20°C to 50°C		
<i>Rated Life</i>	50,000Hrs (L70)		

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-PTRC-40W	8 - CRI 80+	30 - 3000K	60 - 60Deg
BLU-PTRC-50W		40 - 4000K	90 - 90Deg
BLU-PTRC-60W		50 - 5000K	110 - 110Deg

Example: BLU-PTRC-40W-827-827-60

Specification subject to change without notice