



TECHNICAL DATA

| | | | |
|----------------------------|-------------------------|---------|---------|
| <i>Product Code</i> | BLU-PTRC2 | | |
| <i>Wattage</i> | 80W / 100W / 120W | | |
| <i>Luminous Flux</i> | 80W | 100W | 120W |
| | 3000K – 10980lm | 12745lm | 14705lm |
| | 4000K – 11090lm | 12870lm | 14850lm |
| | 5000K – 11200lm | 13000lm | 15000lm |
| <i>Luminous Efficacy</i> | >140lm/W | | |
| <i>SDCM</i> | <5 | | |
| <i>CRI</i> | >80 | | |
| <i>Beam Angle</i> | 60°/90°/110° | | |
| <i>Power Factor</i> | >0.95 | | |
| <i>Working Voltage</i> | 220-240 VAC, 50/60Hz | | |
| <i>LED Driver</i> | Integral | | |
| <i>Control</i> | Switched / 1-10V / DALI | | |
| <i>Body Material</i> | Die-cast Aluminium | | |
| <i>Optics</i> | PMMA | | |
| <i>IP Rating</i> | IP66 | | |
| <i>Working Temperature</i> | -20°C to 50°C | | |
| <i>Rated Life</i> | 50,000Hrs (L70) | | |

ORDER INFORMATION

| Product Code | X | YY | ZZ |
|---------------------|-------------|------------|--------------|
| BLU-PTRC2-80W | 8 - CRI 80+ | 30 - 3000K | 60 - 60Deg |
| BLU-PTRC2-100W | | 40 - 4000K | 90 - 90Deg |
| BLU-PTRC2-120W | | 50 - 5000K | 110 - 110Deg |

Example: BLU-PTRC2-80W-827-60

Specification subject to change without notice