



**TECHNICAL DATA**

<i>Product Code</i>	BLU-STREETZ		
<i>Wattage</i>	30W / 50W / 70W		
<i>Luminous Flux</i>	30W	50W	70W
	3000K – 3825lm	6370lm	8920lm
	4000K – 3900lm	6500lm	9100lm
<i>Luminous Efficacy</i>	>130lm/W		
<i>SDCM</i>	<5		
<i>CRI</i>	>70		
<i>Beam Angle</i>	T1/T2/T3		
<i>Power Factor</i>	>0.95		
<i>Working Voltage</i>	220-240 VAC, 50/60Hz		
<i>LED Driver</i>	Integral		
<i>Control</i>	Switched / 1-10V / DALI		
<i>Body Material</i>	Die-cast Aluminium		
<i>Optics</i>	PMMA		
<i>IP Rating</i>	IP66		
<i>Working Temperature</i>	-20°C to 50°C		
<i>Rated Life</i>	50,000Hrs (L70)		

**ORDER INFORMATION**

<b>Product Code</b>	<b>X</b>	<b>YY</b>	<b>ZZ</b>
BLU-STREETZ-30W	8 - CRI 80+	30 - 3000K	T1 - T1Deg
BLU-STREETZ-50W		40 - 4000K	T2 - T2Deg
BLU-STREETZ-70W			T3 - T3Deg

Example: BLU-STREETZ-30W-830-T1

*Specification subject to change without notice*