



## TECHNICAL DATA

|                     |  |
|---------------------|--|
| Product Code        | BLU-DOUP-R13   |
| Wattage             | 42W  |
| Luminous Flux       | 2700K – 3470 lm<br>3000K – 3510 lm<br>4000K – 3550 lm<br>6000K – 3590 lm |
| Luminous Efficacy   | >80lm/W  |
| SDCM                | <3   |
| CRI                 | >83  |
| Beam Angle          | 15°/24°/38°  |
| Power Factor        | >0.95  |
| Working Voltage     | 24 VDC/240 VAC, 50/60Hz  |
| LED Driver          | Integral   |
| Control             | Switched   |
| Body Material       | Extruded aluminium alloy #6063   |
| Optics              | Clear  |
| IP Rating           | IP65   |
| Working Temperature | -20°C to 50°C  |
| Rated Life          | 50,000Hrs (L70)  |

## ORDER INFORMATION

| Product Code     | X           | YY   | ZZ  |
|------------------|-------------|--|---|
| BLU-DOUP-R13-42W | 8 - CRI 80+ | 27 - 2700K<br>30 - 3000K<br>40 - 4000K<br>60 - 6000K | 15 - 15 Deg<br>24 - 24 Deg<br>38 - 38 Deg |

Example: BLU-DOUP-R13-42W-827-15

Specification subject to change without notice