



### TECHNICAL DATA

<i>Product Code</i>	BLU-WIND-18	
<i>Wattage</i>	18W / 25W	
<i>Luminous Flux</i>	18W	25W
	2700K – 1200lm	1600lm
	3000K – 1225lm	1625lm
	4000K – 1250lm	1650lm
	6000K – 1300lm	1750lm
<i>Luminous Efficacy</i>	>65lm/W	
<i>SDCM</i>	<3	
<i>CRI</i>	>83/93	
<i>Working Voltage</i>	40-45V / 29-32V DC	
<i>LED Driver</i>	Remote	
<i>Control</i>	Switched / 1-10V / DALI	
<i>Body Material</i>	Die-cast Aluminium	
<i>Optics</i>	PC diffuser with Specular Reflector	
<i>IP Rating</i>	IP40	
<i>Working Temperature</i>	-20°C to 40°C	
<i>Rated Life</i>	50,000Hrs (L70)	

### ORDER INFORMATION

<b>Product Code</b>	<b>X</b>	<b>YY</b>
BLU-WIND-18-18W	8 - CRI 83+	27 - 2700K
BLU-WIND-18-25W	9 - CRI 93+	30 - 3000K
		40 - 4000K
		60 - 6000K

Example: BLU-WIND-18-18W-827

Specification subject to change without notice