



Beam R16

Outdoor Series



TECHNICAL DATA

<i>Product Code</i>	BLU-BEAM-R16
<i>Wattage</i>	44W
<i>Luminous Flux</i>	2700K – 3930lm 3000K – 3970lm 4000K – 4010lm 6000K – 4050lm
<i>Luminous Efficacy</i>	>90lm/W
<i>SDCM</i>	<3
<i>CRI</i>	>83
<i>Beam Angle</i>	9°/15°/20°/30°/45°
<i>Power Factor</i>	>0.95
<i>Working Voltage</i>	240 VAC, 50/60Hz
<i>LED Driver</i>	Integral
<i>Control</i>	Switched
<i>Body Material</i>	12# Die-casting dark grey powder coated aluminium
<i>Optics</i>	PMMA with tempered glass cover
<i>IP Rating</i>	IP66
<i>Working Temperature</i>	-20°C to 50°C
<i>Rated Life</i>	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-BEAM-R16-44W	8 - CRI 83+	27 - 2700K 30 - 3000K 40 - 4000K 60 - 6000K	9 - 9Deg 15 - 15Deg 20 - 20Deg 30 - 30Deg 45 - 45Deg

Example: BLU-BEAM-R16-44W-827

Specification subject to change without notice