



TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø X H)mm	Cut out (mm)
		2700K	3000K	4000K	5000K		
BLU-COMFY-10	16W	1410	1440	1470	1500	105 X 90	90
BLU-COMFY-12	24W	2080	2120	2165	2210	125 X 117	115
BLU-COMFY-16	28W	2430	2480	2530	2580	138 X 122	150
BLU-COMFY-19	28W	2430	2480	2530	2580	165 X 140	170
BLU-COMFY-19	32W	2780	2835	2890	2950	165 X 140	170
BLU-COMFY-23	35W	3030	3090	3155	3220	233 X 177	210
BLU-COMFY-23	42W	3635	3710	3785	3865	233 X 177	210

Luminous Efficacy

SDCM

CRI

Beam Angle

Working Voltage

LED Driver

Control

Body Material

Optics

IP Rating

Working Temperature

Rated Life

>85lm/W

<3

>83/93

15°/24°/38°/60°

36 VDC

Remote

Switched / 1-10V / DALI

Die-cast Aluminium

PMMA

IP40

-20°C to 40°C

50,000Hrs (L70)

ORDER INFORMATION

Product Code

BLU-COMFY-10-16W

BLU-COMFY-12-24W

BLU-COMFY-16-28W

BLU-COMFY-19-28W /32W

BLU-COMFY-23-35W / 42W

X

8 - CRI 83+

9 - CRI 93+

YY

27 -2700K

30 -3000K

40 -4000K

50 -5000K

ZZ

15 - 15 Deg

24 - 24 Deg

38 - 38 Deg

60 - 60 Deg

Example: BLU-COMFY-10-16W-827-15

Specification subject to change without notice