



Deimos 28C



TECHNICAL DATA

| Code | Wattage | Luminous Flux | | | | Size |
|----------|---------|---------------|-------|-------|-------|----------------|
| | | 2700K | 3000K | 4000K | 6000K | L x W x H (mm) |
| DEIM-28C | 30W | 2250 | 2300 | 2350 | 2400 | 280x280x75 |

| | |
|----------------------------|----------------------|
| <i>Luminous Efficacy</i> | >75lm/W |
| <i>SDCM</i> | <3 |
| <i>CRI</i> | >80 |
| <i>Beam Angle</i> | 120° |
| <i>Power Factor</i> | >0.95 |
| <i>Working Voltage</i> | 220-240 VAC, 50/60Hz |
| <i>LED Driver</i> | Integral |
| <i>Control</i> | Switched |
| <i>Body Material</i> | Die-cast Aluminium |
| <i>Diffuser</i> | Polycarbonate |
| <i>IP Rating</i> | IP65 |
| <i>Working Temperature</i> | -20°C to 50°C |
| <i>Rated Life</i> | 50,000Hrs (L70) |

ORDER INFORMATION

| Product Code | X | YY | ZZ |
|------------------|-------------|--|------|
| BLU-DEIM-28C-30W | 8 - CRI 80+ | 27 -2700K 30 -3000K 40 -4000K 60 -6000K | IP65 |

Example: BLU-DEIM-28C-30W-827-IP65

Specification subject to change without notice