


ECO HE

High Efficiency Weatherproof



TECHNICAL DATA


Code	Wattage	Luminous Flux				Size (L X W X H)mm
		2700K	3000K	4000K	6000K	
ECO-HE-120	35	4220	4260	4300	4340	1260 X 135 X 95
ECO-HE-120	40	4820	4860	4900	4940	1260 X 135 X 95
ECO-HE-120	48	5780	5820	5840	5880	1260 X 135 X 95
ECO-HE-150	52	6260	6300	6340	6380	1500 X 135 X 95
ECO-HE-150	60	7240	7280	7320	7360	1500 X 135 X 95
ECO-HE-150	65	7820	7860	7900	7960	1500 X 135 X 95



Length: 1260 /1500 mm

Width: 135 mm

Height: 95 mm



<i>Luminous Efficacy</i>	>120lm/W
<i>SDCM</i>	<3
<i>CRI</i>	>83
<i>Beam Angle</i>	120°
<i>Working Voltage</i>	100-240V AC, 50/60Hz
<i>LED Driver</i>	Integral
<i>Control</i>	Switched
<i>Body Material</i>	Polycarbonate
<i>Diffuser</i>	Polycarbonate
<i>IP Rating</i>	IP65
<i>Working Temperature</i>	-20°C to 50°C
<i>Rated Life</i>	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
ECO-HE-120-35W	8 - CRI 83+	27 -2700K	IP65 - IP65
ECO-HE-120-40W		30 -3000K	
ECO-HE-120-48W		40 -4000K	
ECO-HE-150-52W		60 -6000K	
ECO-HE-150-60W			
ECO-HE-150-65W			

Example: BLU-ECO-HE-120-35W-827-IP65

Specification subject to change without notice