



TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø X H)mm	Cut out (mm)
		2700K	3000K	4000K	5000K		
BLU-FOCAL-8	8W	720	740	760	780	83 X 73	75
BLU-FOCAL-11	20W	1820	1840	1860	1880	110 X 105	95
BLU-FOCAL-14	28W	2560	2590	2620	2650	148 X 100	130

Luminous Efficacy

>90lm/W

SDCM

<3

CRI

>83/93

Beam Angle

24°/38°

Working Voltage

36 VDC

LED Driver

Remote

Control

Switched / 1-10V / DALI

Body Material

Aluminium

Diffuser

Clear / Frosted Glass

Reflector

Aluminium

IP Rating

IP44 / IP65

Working Temperature

-20°C to 40°C

Rated Life

50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-FOCAL-8-8W	8 - CRI 83+	27 -2700K	24 - 24 Deg
BLU-FOCAL-11-20W	9 - CRI 93+	30 -3000K	38 - 38 Deg
BLU-FOCAL-14-28W		40 -4000K	
		50 -5000K	

Example: BLU-FOCAL-8-8W-827-24

Specification subject to change without notice