



### TECHNICAL DATA

<i>Product Code</i>	BLU-GFLX-1515V	
<i>Wattage</i>	7.2W & 12W	
<i>Luminous Flux</i>	7.2W	12W
	2700K – 590lm	990lm
	3000K – 620lm	1020lm
	4000K – 650lm	1050lm
	6000K – 680lm	1080lm
<i>Luminous Efficacy</i>	>80lm/W	
<i>SDCM</i>	<3	
<i>CRI</i>	>83/93	
<i>Beam Angle</i>	140°	
<i>Working Voltage</i>	24VDC	
<i>LED Driver</i>	Remote	
<i>Control</i>	Switched / 1-10V / DALI / DMX / SPI	
<i>Body Material</i>	Silicone	
<i>Optics</i>	Silicone	
<i>IP Rating</i>	IP67	
<i>Working Temperature</i>	-20°C to 50°C	
<i>Rated Life</i>	50,000Hrs (L70)	

### ORDER INFORMATION

<b>Product Code</b>	<b>X</b>	<b>YY</b>	<b>ZZ</b>
BLU-GFLX-1515V-7.2W	8 - CRI 83+	27 - 2700K	IP67
BLU-GFLX-1515V-12W	9 - CRI 93+	30 - 3000K	
		40 - 4000K	
		60 - 6000K	

Example: BLU-GFLX-1515V-12W-827-IP67

Specification subject to change without notice