



TECHNICAL DATA

Code	Wattage	Luminuous Flux				Size (A X B X C)mm
		2700K	3000K	4000K	5000K	
MIRROZ-L48	8W	900	920	940	960	480 X 77 X 61
MIRROZ-L60	12W	1380	1400	1420	1440	600 X 77 X 61
MIRROZ-L90	15W	1720	1740	1760	1780	900 X 77 X 61

<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	120°
<i>Working Voltage</i>	240V AC, 50/60Hz
<i>LED Driver</i>	Integral
<i>Power Factor</i>	>0.95
<i>Control</i>	Switched
<i>Body Material</i>	Polycarbonate
<i>Diffuser</i>	Polycarbonate
<i>IP Rating</i>	IP44
<i>Working Temperature</i>	-20°C to 40°C
<i>Rated Life</i>	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
MIRROZ-L48-8W	8 - CRI 83+	27 -2700K	IP44 - IP44
MIRROZ-L60-12W	9 - CRI 93+	30 -3000K	
MIRROZ-L90-15W		40 -4000K	
		50 -5000K	

Example: BLU-MIRROZ-L48-8W-827-IP44

Specification subject to change without notice