



TECHNICAL DATA

| Code | Wattage | Luminous Flux | | | | Size (Ø X H)mm | Cut out (mm) |
|--------------|---------|---------------|-------|-------|-------|-------------------|-----------------|
| | | 2700K | 3000K | 4000K | 6000K | | |
| BLU-VALUE-14 | 12W | 1120 | 1140 | 1160 | 1180 | 145 X 56 | 130 |
| BLU-VALUE-16 | 15W | 1340 | 1360 | 1380 | 1400 | 160 X 66 | 140 |
| BLU-VALUE-19 | 18W | 1670 | 1690 | 1710 | 1730 | 190 X 77 | 165 |
| BLU-VALUE-23 | 23W | 2140 | 2160 | 2180 | 2200 | 230 X 82 | 200 |

Luminous Efficacy

>90lm/W

SDCM

<3

CRI

>83/93

Beam Angle

80°

Working Voltage

25-59 VDC

LED Driver

Remote

Control

Switched / 1-10V / DALI

Body Material

Aluminium

Optics

PC Diffuser

Reflector

Specular Aluminium / Matt Aluminium

IP Rating

IP44

Working Temperature

-20°C to 40°C

Rated Life

50,000Hrs (L70)

ORDER INFORMATION

Product Code

BLU-VALUE-14-12W

BLU-VALUE-16-15W

BLU-VALUE-19-18W

BLU-VALUE-23-23W

X

8 - CRI 83+

9 - CRI 93+

YY

27 -2700K

30 -3000K

40 -4000K

60 -6000K

Example: BLU-VALUE-14-12W-827

Specification subject to change without notice