




TECHNICAL DATA



| Code | Wattage | Luminous Flux | | | | Size (L X H)mm | Cut out (mm) |
|--------------|---------|---------------|-------|-------|-------|----------------|--------------|
| | | 2700K | 3000K | 4000K | 6000K | | |
| BLU-GAIN-S7 | 5W | 425 | 450 | 475 | 500 | 70 X 22 | 63 |
| BLU-GAIN-S11 | 8W | 680 | 720 | 760 | 800 | 110 x 24 | 95 |
| BLU-GAIN-S11 | 10W | 850 | 900 | 950 | 1000 | 110 x 24 | 95 |
| BLU-GAIN-S14 | 12W | 1020 | 1080 | 1140 | 1200 | 140 x 25 | 125 |
| BLU-GAIN-S14 | 15W | 1275 | 1350 | 1425 | 1500 | 140 x 25 | 125 |
| BLU-GAIN-S16 | 15W | 1275 | 1350 | 1425 | 1500 | 160 X 26 | 140 |
| BLU-GAIN-S16 | 18W | 1530 | 1620 | 1710 | 1800 | 160 X 26 | 140 |
| BLU-GAIN-S23 | 23W | 1955 | 2070 | 2185 | 2300 | 230 X 28 | 200 |
| BLU-GAIN-S23 | 30W | 2550 | 2700 | 2850 | 3000 | 230 X 28 | 200 |

| | |
|---------------------|-------------------------|
| Luminous Efficacy | >85lm/W |
| SDCM | <3 |
| CRI | >83/93 |
| Beam Angle | 90° |
| Working Voltage | 36 VDC |
| LED Driver | Remote |
| Control | Switched / 1-10V / DALI |
| Body Material | Die-cast Aluminium |
| Diffuser | Polycarbonate |
| IP Rating | IP44 |
| Working Temperature | -20°C to 40°C |
| Rated Life | 50,000Hrs (L70) |

ORDER INFORMATION

| Product Code | X | YY | ZZ |
|------------------|-------------|-----------|-------------|
| BLU-GAIN-S7-5W | 8 - CRI 83+ | 27 -2700K | IP44 - IP44 |
| BLU-GAIN-S11-8W | 9 - CRI 93+ | 30 -3000K | |
| BLU-GAIN-S11-10W | | 40 -4000K | |
| BLU-GAIN-S14-12W | | 60 -6000K | |
| BLU-GAIN-S14-15W | | | |
| BLU-GAIN-S16-15W | | | |
| BLU-GAIN-S16-18W | | | |
| BLU-GAIN-S23-23W | | | |
| BLU-GAIN-S23-30W | | | |

Example: BLU-GAIN-S7-5W-827-IP44

Specification subject to change without notice