



TECHNICAL DATA

Code	Wattage	Luminuous Flux				Size (Ø X A X H)mm
		2700K	3000K	4000K	6000K	
BEAM-P-R12	6 X 3W	1550	1590	1630	1670	120 X 140 X 150
BEAM-P-R12	6 X 4W	2070	2110	2150	2190	120 X 140 X 150
BEAM-P-R15	12 X 3W	3100	3140	3180	3220	150 X 150 X 180
BEAM-P-R19	18 X 3W	4650	4690	4730	4770	190 X 190 X 220
BEAM-P-R23	36 X 3W	9290	9330	9360	9400	230 X 225 X 270

<i>SDCM</i>	<3
<i>CRI</i>	>83/93
<i>Beam Angle</i>	6°/8°/10°/15°/30°/45°/60°
<i>Working Voltage</i>	240V AC, 50/60Hz
<i>LED Driver</i>	Integral
<i>Power Factor</i>	>0.95
<i>Control</i>	Switched / 1-10V / DALI
<i>Body Material</i>	Die Cast Aluminium
<i>Diffuser</i>	Tempered Glass
<i>IP Rating</i>	IP66
<i>Working Temperature</i>	-20°C to 50°C
<i>Rated Life</i>	50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-BEAM-P-R12-18W	8 - CRI 83+	27 -2700K	6 - 6 Deg
BLU-BEAM-P-R12-24W	9 - CRI 93+	30 -3000K	8 - 8 Deg
BLU-BEAM-P-R15-36W		40 -4000K	10 - 10 Deg
BLU-BEAM-P-R19-54W		60 -6000K	15 - 15 Deg
BLU-BEAM-P-R23-108W			30 - 30 Deg
			45 - 45 Deg
			60 - 60 Deg

Example: BLU-BEAM-P-R12-18W-827-8-IP66

Specification subject to change without notice